

HV-7600SX

high resolution SXGA presenter



- The first 2Mega pixel presenter in the market with true SXGA resolution
- 1/1.8" 2,110,000(1,688x1,248) pixels Progressive Scan CCD
- Excellent picture quality with 900 x 900 TV lines (H)
- F.A.M. (Frame Accumulate Mode) for high-definition still image capture
- Highlighted Zoom Window (Patented)
- Useful Pointing Marker function (Patented)
- Split screen function
- Drawing tools for effective presentation
- 8 image memory
- User preset: 8 modes
- Image download to a PC by Image Mate

SPECIFICATIONS

Image pick-up element	1/1.8 " progressive Scan CCD
Total picture elements	1.688 x 1.248, 2.110.000
Effective picture elements	1525 x 1220 (SXGA), 1600x1200 (XGA)
Resolution (RGB)	>900 (H) x 900 (V)
Resolution (Video)	>470 (H) x 470 (V)
Close-up lens	0
Frame rate	15 Frames / s
Optical zoom	10x (with double speed function)
Digital zoom	2x (can be scrolled by mouse)
Lens	7,2-72 mm, F=3,1
Focusing	Auto / Manual
Shooting area (Minimum)	41 x 33 mm (SXGA), 43x 32 mm (XGA)
Shooting area (Maximum)	362 x 290 mm (SXGA), 380 x 285 (XGA)
Iris	Auto (with level adjustment) / Manual
White balance	Auto / One Push / Manual
Nega/Posi conversion	0
Colour/B&W selection	0
Gamma adjustment	8 position
Freeze function	0
On Screen Display (OSD)	0
Image rotation	270°
Camera head rotation	0
Sync. system	Internal
Text mode (Contrast)	0
F.A.M. (Frame Accumulate Mode)	0
Split Screen	0
Pointing marker	0
Image memory	8 images
Scrolling	0
Edge Enhancement	0
User pre-set	8 settings

Input selection	Internal/RGB1/RGB2
RGB input	2x Mini DSUB 15 Pin
Mic. Input	6,4mm jack
Audio input	2x 3,5 mm Mini-jack
RGB output	Mini DSUB 15 Pin
Output signal	1280 x 1024 (SXGA/60Hz), 1024 x 768 (XGA / 60 Hz), VESA
External RGB signal down convert	O
C-Video output	PAL / NTSC
S-Video output	PAL / NTSC
12VDC out terminal	O
RS-232C control terminal	DSUB 9 Pin
USB terminal	Type B
PC link software	Image Mate
Lighting unit	Upper light / Base light
Mouse	O
Wireless remote controller	O
Power source	AC100-240V, 50/60Hz
Power consumption	0.45 - 0.8A
Dimensions (WxDxH) mm	697 x 541 x 629 (Set-up) 400x 541 x 197 (Folded)
Weight	10 kg

Weight and Dimensions are approximate. Design and specifications are subject to change without prior notice.

Distribué par :  **12-16, rue de Vincennes**
93102 Montreuil cedex
Tél : 01 48 70 90 89
E-mail : contact@cbi-technologies.com
Site Web : www.cbi-technologies.com